



Temperature range +10° C to -18° C



Suitable for solar operation



12/24 V DC and 110- 240V AC

Protective cover and fixing kit  
as accessory

CF special electronics

## COOLMATIC® by WAECO

### COOLMATIC CF-35

- Gross capacity:** 31 litres
- Voltage:** 12/24 volts DC and 110-240 volts AC
- Average power consumption:** 45 watts
- Average running time:** 15% at 20°C ambient temperature, 19% at 32°C ambient temperature, both at 5°C interior temperature
- Power consumption:** Power input x average running time
- Temperature range:** +10°C to -18°C, variable via electronic thermostat with LED indicator
- Insulation:** CFC-free polyurethane foam
- System:** Fully hermetic Danfoss BD35F compressor with integrated control electronics, low-voltage protection adjustable for consumer or starter battery by means of a slide switch, electronic fuse/automatic reverse pole protection, dynamically ventilated wire condenser, aluminium rollbond evaporator
- Material:** Cabinet: PP, lid: PE
- Colour:** Body: pale grey/dark grey, lid: dark grey
- Weight:** approx. 15 kg
- Quality features:** Detachable lid (lid mount at the front), interior light, vertical space for standing 1.5-litre bottles, CF-Spezialelektronik
- Scope of delivery:** DC and AC connection cables, evaporator grille, detachable carrying handles
- Test marks:** TÜV/GS, e-approved according to 95/54/EC (EMC guidelines for vehicles)
- Optional extra:** *High-quality insulating protective cover, Universal fixing kit*