

# OMNISTOR•5002



Elegant design

Security Locks on both sides

Ultra-rapid gear

Fully equipped



The Omnistor 5002 now fits even more elegantly within the current design of motorhomes due to its renewed end caps and modern design! This awning has all the excellent features of an Omnistor awning and presents a modern and elegant appearance!

- Operation** The major advantages are an ultra rapid gear (1) (one third less rotations), the user-friendly telescopic hand crank (up to 155cm!), a built-in end stroke which ensures that the fabric cannot be rolled up incorrectly and the well known Quick Lock System for easy adjustment of the support arms.
- Construction** The retractable arms have twin cables for maximum fabric tension and the redesigned front profile ensures perfect closing every time. A double security lock on both sides of the front profile avoids the unwanted opening of the awning whilst travelling. The roller tube has a 48mm diameter.
- Installation** Standard installation is done by hooking the awning into the existing rail (2) or by means of an adapter set with counterplates, supplied as standard (3). Other adapters page 26 & 27.
- Comfort** Two clips for storing the hand crank are supplied as standard (4)! Also supplied as standard are items for the installation of a Safari-Residence or a Safari-Room by means of clips. The support arms can be installed to the vehicle wall by using the mounting brackets supplied or to the ground.
- Extra** For awnings of **4m length upwards** a tension rafter is supplied as standard. Built-in 12V motors with emergency operation are available from **2,65m length upwards**.  
**The motor cannot be installed retrospectively on a manual awning!**  
**New:** the Omnistor 5002 OTD (1,40m) is a short version for installation above the door.  
**New:** the Omnistor 5002 is available with anodised box in fabrics 03 and 04.
- Colours**

03 >	Blue Sky	04 >	Alaska Grey
18 >	Bahamas Turquoise	20 >	Miami Grey
22 >	Ral 9002	21 >	Orlando
27 >	Curaçao Blue		



(1)



(2)



(3)



(4)



(5)

