

# SAFARI•ROOM

Create additional living space

Available for all Omnistor awnings

Quick installation

Top quality fabric

A Safari-Room consists of two separate PVC side panels and a front panel which can be used as a complete unit or as individual parts. Available for all types of Omnistor awnings except for the Omnistor 9005 and Caravan style.

• **Installation** The front is slid into the lead rail of the awning. The side panels are hung up by means of poles introduced between the box and lead rail.

The side panels are joined to the front profile by means of a synthetic double profile (1).

The awning fabric is joined to the side panel by using the tent clips (2). The anti-slip strips joined with the clips ensure a more wind proof connection.

The connection with the vehicle is done by joining a standard supplied mast with the foamband of the side panel. The open space between vehicle and ground can be overcome by installing the standard supplied windslip.

Under normal circumstances a Safari-Room can be installed in only 15 minutes.

• **Comfort** From 3m onwards the front panel window has a zipper (3). The left hand side panel has a mosquito screen and PVC curtain (4).

• **Extra** Optional curtains available in blue or grey. **For 5 metre and upwards always order a 4 curtain set!**  
A horizontal tension rafter which gives an increased fabric tension is optional. **art.nr.51404800.**

• **Colours**

03 >	Blue Sky	04 >	Alaska Grey
18 >	Bahamas Turquoise	20 >	Miami Grey
22 >	Ral 9002	21 >	Orlando
27 >	Curaçao Blue		



(1)



(2)



(3)



(4)



(5)



*Tip: use a **Hold Down Kit** to prevent the awning and Safari-Room from flying up. See page 28.*